

# Scata™



## INNEVÄGG 07

### WASHABLE WATERBORNE ACRYLIC INDOOR PAINT

#### Product type

Washable waterborne paint with good resistance for ground- and finishpainting in dry areas indoor.

#### Application

Specially aimed for finishtreatment on walls where a warm semimatt surface with good resistance and washability is requested. Can also be used for ground-treatment.

#### Special properties

A paint of high quality with a precise viscosity to allow application without splashes. High covering and filling capability. Resistant against normal household chemicals during limited time. NFE0-free and solvent-free. Is a part of Colorex-MIX tinting system.

## Application data sheet

### Surface preparation

The substrate which shall be painted shall be clean, with good adhesion, dry and dustfree. Wash, flush and remove old paint with bad adhesion. Glossy surfaces shall be sanded mat.

### Application

The paint is ready to use. Apply with roller or brush. After light diluting with water, it can also be applied by spraying. When applying tinted paint always try to apply complete areas with paint from the same can. The paint has a soft structure in order to achieve an even and hiding surface. In order to get an even result, when the paint is applied by roller, it is important that the roller is moved with soft pressure in the same direction over the surface. The same paint can be used both as ground- and top-coat. Recommended is 1-2 layer, depending on type and colour of surface which shall be painted.

### Coating conditions

Apply under controlled conditions, where air-, paint- and surfacetemperature never may be below +5°C. At very high humidity dryingtime will be longer.

## Technical data

Covering	Depending on type of surface, 4-8 m <sup>2</sup> /liter
Resin	Styrolacrylic
Solid content	36 % pro volume
Density	1,4 kg/liter
Viscosity	140 cP
Thinner/cleaner	Water
Application	Roller, brush or spraying
Drying time (it is advisable to indicate the temperature and humidity, at which the data are presented)	Touch dry 1 hour Totally dry 3 hours At 20°C and max 85% humidity
Gloss	6-8 measured at Gardner 60°
Colour	White Base A
Washability	5000 laps according ISO 6504-3. Class 2 acc. DIN 13399
Storage time	2 year in unopened can, frostless
Packaging	9L, 2,73L, 0,9L



#### Individual safety

Avoid skin and eye contact and inhalation of dust and spray mist.

#### Environmental protection

Do not allow into drains or water courses.  
Dispose in accordance with regulations from authorities