



LACKFÄRG 30/90

SOLVENTBASED INDOOR ALKYD ENAMEL

Product type

Solventbased opaque pigmented enamel based on urethan alkyd for in- and outdoor use.

Application

Enamel suitable as ground- and finish-treatment with brush, spraying or roller. E.g. on carpentries, mouldings, furnitures, skirting-board, radiators and other wood- or metalsurfaces indoors.

Special properties

Lackfärg meet the highest demands for nice flow and gloss and is hard and flexible at the same time. It has a very low yellowing-tendency and leaves a hard surface which is easy to clean. Easy to apply also on horizontal surfaces. It is a part of Colorex-MIX tinting system..



Application data sheet

Surface preparation

The substrate which shall be painted shall be clean, with good adhesion, dry and dustfree. Wash, flush and remove old paint with bad adhesion. Clean ev. oilspots with solvent. Glossy surfaces shall be sanded mat. Untreated wood shall be grounded with Snickerigrund. Uneven surfaces shall be treated with putty and sanded and wiped clean before overpainted with Lackfärg.

Application

The paint is ready to use. Apply with brush or suitable enamel-roller. After light diluting with white spirit it can also be applied by spraying. When applying tinted paint always try to apply complete areas with paint from the same can. Recommended is 1-2 layer, depending on type and colour of surface which shall be painted.

Coating conditions

Apply under controlled conditions, where air-, paint- and surfacetemperature never may be below +5°C. At low temperatures the dryingtime will be longer.

Technical data

Covering	Depending on type of surface, 7-10 m ² /liter
Resin	Uretan-alkyd
Solid content	49 % pro volume
Density	1,3 kg/liter
Viscosity	340 cP
Thinner/cleaner	White Spirit
Application	Brush, roller or spraying
Drying time (it is advisable to indicate the temperature and humidity, at which the data are presented)	Touch dry/repaintable 6 hour Totally dry 24 hours At 20°C and max 85% humidity
Gloss	40 halfglossy, 80 glossy, measured at Gardner 60°
Colour	White Base A
Washability	10.000 laps according ISO 6504-3. Class 1 acc. DIN 13399
Storage time	2 year in unopened can, frostless
Packaging	,2,73L, 0,9L

Eco – signs

Individual safety

Not expected to cause any adverse health effects when used as intended. Avoid skin and eye contact. Avoid the inhalation of dust, particulates and spray mist arising from the application of this preparation

Environmental protection

The product is not classified as dangerous for the environment. The product should not be allowed to enter drains or water courses. **Do not allow into drains or water courses. Dispose in accordance with regulations from authorities**