



DATA SHEET

TAKALKYD

Area of use

Solventbased paint for ground- and finishpainting of walls and ceilings in dry areas indoor. Specially aimed for areas where a waterbourne paint can not be used. E.g. surfaces damaged by smoke, nicotin, soot etc. where there is a risk for "bleeding". Also surfaces which has a low binding, e.g. old gluepaint or chalkpaint can be treated with Takalkyd.

Special properties

A traditionell alkydpaint with a mat surface without lightreflektion mainly ment for ceilings. Can be used indoors everywhere where its special properties are necessary. As solvent is only used white spirit free from aromates.

How to use

The substrate which shall be painted shall be clean, with good adhesion, dry and dustfree. Wash, flush and remove old paint with bad adhesion. Glossy surfaces shall be sanded mat. Apply with roller or brush. After light diluting with white spirit, it can also be applied by spraying. The paint has a soft structure in order to achieve an even and hiding surface. In order to get an even result, when the paint is applied by roller, it is important that the roller is moved with soft pressure in the same direction over the surface. If you want to apply more than one layer Takalkyd has to dry minimum 12 hour between the layers.

Technical Data

Resin:	Alkyd resin	YSAM-gr./YL-gr.:	2/00
Gloss:	3 mat (depends on number of layer and substrate) acc. SS-184184	Viscosity:	210 cP, Light tixotropic
Density:	1,51acc. to SS-184111	Flammable:	2b, flashpoint +40°C
Solid content:	51 volume-%	Storage time:	2 year in unopened can
Thinner/Cleaning:	White spirit	Application:	Brush, roller or spraying
Covering:	5-9 m ² /lit	Colour:	White
Drying time:	4-8 hour touchdry 12 – 16 hour dry, depending on temperature and humidity.	Packaging:	1, 2.5 and 10
Washability:	> 10.000 laps acc.SS-184164	Fillingdegree:	100 %
		Application temp.:	Minimum + 4°C